

MATERIAL SAFETY DATA SHEET



Product number SS945

1. Product and Company Identification

Product name SS945 Dry Silicone Spray
Effective date 14-Jul-2022
Company information SPRAYWAY SINGAPORE PTE LTD
Company phone 65-6744 3075
Version # 01

2. Hazards Identification

Emergency overview Aerosol. CONTENTS UNDER PRESSURE.
Irritating to eyes. Irritating to respiratory system. EXTREMELY FLAMMABLE
Prolonged exposure may cause chronic effects.

Potential health effects

Routes of exposure Eye contact. Inhalation. Ingestion.

Eyes Causes eye irritation.

Skin Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Irritating to respiratory system. Prolonged inhalation may be harmful.

Ingestion Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage. Components of the product may be absorbed into the body by ingestion.

Target organs Central nervous system. Lungs.

Chronic effects May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May cause delayed lung injury.

Signs and symptoms Discomfort in the chest. Narcosis. Coughing. Defatting of the skin. Skin irritation.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Dimethyl Ether	115-10-6	20 - 30
Aliphatic Petroleum Solvent	64742-89-8	20 - 30
Silicone oil	63148-62-9	20 - 30
Ordorless Mineral Spirits	64742-48-9	5 - 8

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Continue rinsing.

Skin contact Wash off with warm water and soap. Get medical attention if irritation develops and persists.

Inhalation If symptoms develop move victim to fresh air. For breathing difficulties, oxygen may be necessary. Get medical attention if symptoms persist.

Ingestion Call a physician immediately. Do not induce vomiting without advice from poison control center. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration.

5. Fire Fighting Measures

Flammable properties	Heat may cause the containers to explode. Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.
Extinguishing media	
Suitable extinguishing media	Water. Water spray. Water fog. Carbon dioxide (CO2). Dry chemicals.
Protection of firefighters	
Protective equipment and precautions for firefighters	In case of fire and/or explosion do not breathe fumes. Containers should be cooled with water to prevent vapor pressure build up. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

6. Accidental Release Measures

Methods for containment	Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Prevent entry into waterways, sewer, basements or confined areas.
Methods for cleaning up	Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. After removal flush contaminated area thoroughly with water.

7. Handling and Storage

Handling	Pressurized container: Do not pierce or burn, even after use. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not smoke while using or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not re-use empty containers. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear personal protective equipment. Avoid prolonged exposure.
Storage	Level 3 Aerosol. Contents under pressure. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Avoid exposure to long periods of sunlight. Store in cool place. Store in a well-ventilated place. Keep out of the reach of children. Keep away from food, drink and animal feedingstuffs. Level 3 Aerosol.

8. Exposure Controls / Personal Protection

Exposure Limits

ACGIH

Components	CAS#	TWA	STEL	Ceiling
Propane	74-98-6	1000 ppm	Not established	Not established

OSHA

Components	CAS#	TWA	STEL	Ceiling
Propane	74-98-6	1000 ppm	Not established	Not established

Personal protective equipment

Eye / face protection	Chemical goggles are recommended.
Skin protection	Wear appropriate chemical resistant clothing. Chemical resistant gloves.
Respiratory protection	Wear positive pressure self-contained breathing apparatus (SCBA). If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

9. Physical & Chemical Properties

Appearance	Compressed liquefied gas.
Boiling point	46.4 °F (7.8 °C) estimated

Color	clear colorless
Flammability (HOC)	41.9681 kJ/g estimated
Flash back	Yes
Flash point	-156 °F (-104.4 °C) Propellant
Form	Aerosol.
Odor	solvent
pH	Not applicable
Physical state	Liquid.
Pressure	77 - 87 psig @ 70F
Solubility	Partially
Specific gravity	0.5915 estimated

10. Chemical Stability & Reactivity Information

Incompatible materials Strong oxidizing agents.

11. Toxicological Information

Acute effects Acute LD50: 5928 mg/kg estimated, Rat, Dermal
 Acute LC50: 1316 mg/l/4h estimated, Rat, Inhalation

Component analysis - LD50

Toxicology Data - Selected LD50s and LC50s

Aliphatic Petroleum Solvent	64742-89-8	Oral LD50 Mouse 5000 mg/kg; Dermal LD50 Rabbit 3000 mg/kg
Odorless Mineral Spirits	64742-48-9	Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >3160 mg/kg
Propane	74-98-6	Inhalation LC50 Rat 658 mg/L 4 h

12. Ecological Information

Ecotoxicity LC50 41509 mg/L, Fish, 96.00 Hours,
 EC50 , Daphnia, 48.00 Hours,
 Contains a substance which causes risk of hazardous effects to the environment.

13. Disposal Considerations

Waste codes D001: Waste Flammable material with a flash point <140 F
Disposal instructions Contents under pressure. Dispose of this material and its container to hazardous or special waste collection point. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name	Consumer commodity
Hazard class	ORM-D
Subsidiary hazard class	None

Additional information:

Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None

IMDG

Basic shipping requirements:

Proper shipping name	AEROSOLS
Hazard class	2.1
UN number	1950


Additional information:

Packaging exceptions	LTD QTY
Labels required	None



IATA

Basic shipping requirements: Aerosols, flammable
Proper shipping name 2.1
Hazard class 1950
UN number
Additional information: LTD QTY
Packaging exceptions None
Labels required



15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
 CERCLA/SARA Hazardous Substances - Not applicable.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (Superfund) reportable quantity

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely hazardous substance No

Section 311 hazardous chemical Yes

Hazard categories (311/312) Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - Yes
 Reactivity Hazard - No

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations**U.S. - Pennsylvania - RTK (Right to Know) List**

Aliphatic Petroleum Solvent	64742-89-8	Present
Odorless Mineral Spirits	64742-48-9	Present
Propane	74-98-6	Present

16. Other Information

Further information HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings Health: 1*
 Flammability: 4
 Physical hazard: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available.

Prepared by Regulatory Compliance